

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4002)

Set a fir post, 3 ft. long 4" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ S19 on W & 20 on E faces, from which
A fir, 20" dia., bears N.1°0'E., 44 lks., mkd: ¼ S20 BT.
A fir, 24" dia., bears S.39°30'W., 31 lks., mkd: ¼ S19 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Sept. 1968 - C.S. File 54/72-22

Found - Orig. 20" now 20" Fir snag, N.1°E., 29.0 ft., scribe visible.
Orig. 24" now 24" Fir snag, S.39½°W., 20.5 ft. scribe visible.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T25S R8W
OFFICE 1968 ¼ S19 S20
New BTs- 10" Hemlock N.31°W., 12.4 ft. mkd: ¼ S19 CS BT
8" D.Fir N.61°E., 13.4 ft. mkd: ¼ S20 CS BT
13" Hemlock S.40°E., 18.2 ft. mkd: ¼ S20 CS BT
This corner lies on very steep, south slope.