

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4002-3)

Set a dogwood post, 3 ft. long, 4" sq. 24" in the ground, for cor. of secs. 17, 18, 19, & 20, marked T25S S17 on NE, R8W S20 on SE, S19 on SW & S18 on NW faces; with 3 notches on S & 5 notches on E edges; from which

A fir, 32" dia., bears N.6°30'E., 43 lks., mkd: T25S R8W S17 BT.

A rhododendron, 5" dia., bears S.1°30'E., 25 lks., mkd: T25S R8W S20 BT.

A hemlock, 15" dia., bears S.68°30'W., 15 lks., mkd: T25S R8W S19 BT.

A cedar, 25" dia., bears N.85°W., 34 lks., mkd: T25S R8W S18 BT.

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15050)

The corner of secs. 17, 18, 19, & 20 determined from the remaining orig. BTs:

A fir, 45" dia., bears N.6°30'E., 6 lks., with healed blaze (rec. 43 lks.)

A hemlock 20" dia., bears S.68°30'W., 15 lks., with fragmentary scribe marks visible on partially healed blaze.

A cedar, 30" dia. bears N.85°W., 34 lks., with fragmentary scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T25S R8W
S 18 | S 17
S 19 | S 20
1972

from which

A sandstone boulder, 4x4x6 ft. high, bears S.24½°E., 30½ lks., mkd: X B O on the NE face.