

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4012)

Set fir post, 3 ft. long 4" sq. 24" in the ground for ¼ sec. cor. marked ¼ S6 on W & 5 on E face, from which
A fir, 6" dia., bears N.50°15'E., 10 lks., mkd: ¼ S5 BT.
A fir, 6" dia., bears N.3°W., 28 lks., mkd: ¼ S6 BT.

Donald Peel - For: Weyerhaeuser Co - April 1967- C.S. 55/30-4

Found - GLO Survey Record - Post -- Gone.
6" fir N.50°E. 10 lks, now 13" fir, closed face.
6" fir N.3°W. 28 lks. -- gone.
Set - 4' x 3/4" pipe 3½' in ground & square post.
Re-referenced with 'W' nails & plates only
13" fir N.50°E. 6.2 ft.
14" fir N.21°W. 29.8 ft.

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16459-60)

The ¼ sec. cor. of secs. 5 & 6, perpetuated & recorded by Peel, in 1967, monumented with an iron pipe, ½" dia., firmly set, projecting 4" above ground, from which an original BT:
A fir, 15" dia. bears N.50¼°E., 10 lks. with healed blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, directly over iron pipe, with brass cap mkd:
T25S R8W
1/4
S 6|S 5
1979
from which a new bearing tree
A fir, 8" dia., bears N.58½°W., 13½ lks. mkd: ¼ S6 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2013 - M167-6

Found - 1979 BLM cap and BTS (now snags) as described Vol. 42, pg. 16460.
New BTs- 12" Fir, scribed "S5 ¼ BT", BT tag bears; N.38°51'E. 19.3 ft to spike.
10" Fir, scribed "S6 ¼ BT", BT tag bears; S.17°W., 1.8 ft to spike.