

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4000)

Set hemlock post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. marked ¼ S20 on N & S29 on S face; from which
A fir, 24" dia., bears N.75°E., 113 lks., mkd: ¼ S20 BT.
A fir, 30" dia., bears S.86°30'E., 79 lks., mkd: ¼ S29 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Aug 1968 - C.S. File 54/72-16

Found - Orig. 24" now 28" Fir, alive, N.75°E., 74.6 ft., shows good scar. Also "W" nail.
Orig. 30" now 36" Fir, alive, S.86½°E., 52.1 ft., opened & scribe marks visible. Also "W" nail.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T25S R8W
OFFICE ¼ S 20
1968 S 29
New BTs- 9" Hemlock N.70°E., 25.0 ft. mkd: ¼ S20 CS BT
9" Hemlock S.55°E., 12.2 ft. mkd: ¼ S29 CS BT

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15046-7)

The ¼ sec. cor. of secs. 20 & 29, perpetuated & recorded by Tracy, in 1968, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd. from which the orig. BTs
A fir, 25" dia., bears N.75°E., 113 lks., with healed blaze & a galvanized nail with "W" embossed on head, driven into base.
A fir, 38" dia., bears S.86½°E., 38 lks., with healed blaze & a galvanized nail with "W" embossed on head, driven into base.
and BTs mkd. by Tracy
A hemlock, 8" dia., bears N.69¾°E., 38 lks., with scribe marks ¼ S20 BT visible on open blaze.
A hemlock, 10" dia., bears S.58¾°E., 18½ lks., with scribe marks ¼ S29 CS BTs visible on open blaze.