

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4003)

Set fir post, 3 ft. long, 4" sq. 24" in the ground, for ¼ sec. cor. mkd: ¼ S17 on N & 20 on S face; from which
A fir, 12" dia., bears S.10°E., 30 lks., mkd: ¼ S20 BT.
A cedar, 15" dia., bears N.20°W., 75 lks., mkd: ¼ S17 BT.

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15051)

Point for the ¼ sec. cor. of secs. 17 & 20, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:
¼ $\frac{S\ 17}{S\ 20}$
1972

from which
A hemlock, 6" dia., bears N.55°W., 24½ lks., mkd: ¼ S17 BT
A hemlock, 13" dia., bears S.21°W., 26 lks., mkd: ¼ S20 BT