

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4007)

-----  
Set cedar post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. 800 ft. below sec. cor., marked ¼ S8 on N & 17 on S faces; from which  
    An alder, 8" dia., bears S.75°W., 35 lks. mkd S17 BT.  
    An alder, 10" dia., bears N.30°W., 20 lks. mkd S8 BT

Michael McDowell - For: Weyerhaeuser Co. - March 16, 1977 - C.S. File 58/141

-----  
Set - A 1 3/4" galvanized iron pipe w/brass cap, from which:  
    A 40" fir BT bark scribed bears S.15°E., 20.3 ft.  
    A 24" incense-cedar scribed BT bears N.81°E., 61.5 ft.

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16457-8)

-----  
From the cor. of secs. 8 & 17 only  
N.89°51'W., bet. secs. 8 & 17  
45.25 chains

From this point, a corner established by Reppeto, in 1975, for Weyerhaeuser Timber Co., bears South, 0.075 chs, monumented with an iron post. 2" dia., firmly set, projecting 18" above ground, with brass cap mkd. 25S SW ¼ S8 S17, from which the remains of bearing trees mkd. by Reppeto:

    A fir snag, 42" dia., bears N.15½°E., 42 lks., with a nail with "W" embossed on head, at base.

    A cedar, 32" dia., bears N.80°E., 92 lks., with scribe marks T25S R8W S8 ¼ BT visible on open blaze.

    A fir, 50" dia., bears S.15°E., 32 lks., with scribe marks T25S R8W S17 ¼ BT visible on bark blaze.

    A fir snag. 50" dia., bears N.56½°W., 34 lks., with a nail with "W" embossed on head, at base.

47.99 chains

The ¼ sec. cor. of secs. 8 & 17 determined at rec. distance from the remains of the original BTs

    An alder, 16" dia., bears N.53°W., 20 lks., with illegible scribe marks visible on opened blaze. (Record, N.30°W.)

    An alder snag. 14" dia., bears S.57½°W., 35 lks., with illegible scribe marks visible on opened blaze. (Rec. S.75°W.)

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

At the corner point  
 Set an iron post, 28" long, 2½" dia., 24" in the ground, with  
 brass cap mkd. T25S R8W

¼  $\frac{S \ 8}{S \ 17}$   
 1979

from which new BTs  
 A cedar, 15" dia., bears N.49½°W., 36 lks., mkd. ¼ S8 BT.  
 A cedar, 10" dia., bears S.56½°W., 6½ lks., mkd. ¼ S17 BT.  
 Corner is located 1.50 chs. N. of graveled road, 25 lks.  
 wide, bears N. 45° W. and S. 45° E.

Harry Reppeto - For: Weyerhaeuser Co. - April 29, 1980 - C.S.  
 file 58/141

-----  
 Narrative: During March, 1977, Weyerhaeuser Co. surveyed the  
 boundary common to Secs 8 & 17, T25S., R8W and set the common  
 ¼ corner at the proportionate distance as described in the  
 original CEO survey and recorded same. Subsequently,  
 cadastral surveyors from the Roseburg BLM office uncovered  
 evidence of the original ¼ corner at a point 181.1 ft. west  
 and remonumented it.

On April 29, 1980, we destroyed all evidence of our set  
 corner. Original GLO records called for two alder bearing  
 trees as follows:

- 8" Alder, S.75°W., 35 lks.
- 10" Alder, N.30°W., 20 lks.

We found on 4/29/80:

- BLM brass cap dated 1979 from which:
  - 12" Alder snag OBT with face and BLM tag, S.57½°W., 35 lks
  - 16" Alder OBT, scribing visible and BLM tag, N.50½°W., 20 lks.
  - 8" Red cedar (scribed 1979), S.56½°W., 6½ lks.
  - 14" Red cedar, (scribed 1979), N.49½°W., 36 lks.

DCSO note: The Cadastral survey referred to is unofficial and  
 not yet of record in our office. However, a copy of that  
 particular corner from the 1979 survey was received and is  
 attached to Reppeto's information in the C.S. file 58/141.