

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4010)

Set cedar post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. marked ¼ S5 on N & 8 on S face; from which
A cedar, 10" dia., bears N.20°W., 32 lks., mkd: ¼ S5 BT.
A cedar, 30" dia., bears S.60°E., 17 lks., mkd: ¼ S8 BT.

Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - March 6, 1975 - C.S. File 58/45

Found - 1" iron pipe set by Weyerhaeuser Co.
12" Cedar, W. Co. Tag & "W" nail N.20°W., 27.5 ft.
50" Cedar, W. Co. Tag & "W" nail S.60°E., 9.8 ft.
BLM tags & orig. BTs

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16459)

The ¼ sec. cor. of secs. 5 & 8, perpetuated by person(s) unknown, monumented with an iron pipe, 1" dia., firmly set, projecting 18" above ground, from which the remains of the original bearing trees:

A cedar, 18" dia., bears N.20°W., 41 lks., with scribe marks ¼ S5 BT visible on open blaze. (Record, 32 lks.)
A cedar, 50" dia., bears S.60°E., 17 lks., with healed blaze.

At the corner point

Set an iron post, 28", long, 2½" dia., 24" in the ground with brass cap mkd.

T25S R8W
¼ $\frac{S\ 5}{S\ 8}$

1977

Reset iron pipe alongside iron post.