

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 240640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford
Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958
surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42
Page(s) 16462)

S.89°21'W on the E & W center line of sec. 5

44.32 chains

A corner established by Henry R. Reppeto. Registered Land
Surveyor No. 618, in 1975, monumented with an iron pipe, 1½"
dia., firmly set, projecting 12", above ground, from which
bearing trees mkd. by Reppeto:

A fir, 34" dia., bears N.2°E., 73 lks., with a nail with
"W" embossed on head, at base.

A fir, 27" dia., bears S.41°W., 53 lks., with a nail with
"W" embossed on head, at base.

45.47 chains

Point for the center ¼ sec. cor. of sec. 5, at intersection
with the E. and W. center line.

Set an iron post, 28" long 2½" dia., 24" in the ground, with
brass cap mkd.

T25S R8W
C ¼ S 5
1979

from which

A fir, 13" dia., bears N.55½°E., 12½ lks., mkd. C ¼ S5 BT.

A fir, 20" dia., bears S.30½°W., 48 lks., mkd. C ¼ S5 BT.