

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 5 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - March 6, 1975 - C.S. File 58/45

Set 2" x 3 ft. Iron pipe, one ft. in the ground with a brass cap stamped "N 1/4 S5". Pipe is mounded with rocks.

Referenced by:

50" Fir S.42°E., 26.2 ft. "W" nail, W. Co. tag reads: Sec. 5 T25S R8W 26.2 ft. N.42°W. to N 1/4 Cor., scribed "1/4 S5 BT"

24" Fir S.21°W., 40.8 ft. "W" nail, W. Co. tag reads: Sec. 5 T25S R8W 40.8 ft. N.21°E. to N 1/4 Cor., scribed "1/4 S5 BT"

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16433)

(Page 16433) (3.14 chs.)

A Corner established and recorded by Reppeto in 1975, monumented with an iron post 1 1/2" dia., firmly set, projecting 18" above ground in a mound of stone 3 ft. base, 1 ft. high, with brass cap mkd.

N 1/4
S 5

from which bearing trees mkd. by Reppeto

A Fir 58" dia., bears S.42°E., 44 lks. dist. with scribe marks 1/4 S5 BT on bark.

A Fir 30" dia., bears S.21°W., 64 lks. dist. with scribe marks 1/4 S5 BT on bark.

(5.67 chs.) (S.89°38'W.)

Point for the 1/4 sec. cor. of sec. 5 only.

(Page 16461)

The point for the 1/4 sec. cor. of sec. 5 only, is at proportionate distance on the N. bdy. of sec. 5.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24 S R 8 W
1/4 S 5

T 25 S R 8 W
1979

from which

A Hemlock 10" dia., bears S.11°E., 60 lks. dist. mkd. 1/4 S5 BT.

A Fir 18" dia., bears S.21°W., 20 1/2 lks. dist. mkd. 1/4 S5 BT.

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 5 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2013 - M167-6

Found - 1979 BLM cap, both BTs now stumps.
New BTs- 12" fir, scribed "S5 ¼ BT" BT tag, bears; N.40°52'W,
20.8 ft. to spike.
12" Cedar, scribed "S5 ¼ BT", BT tag bears;
S.80°56'W., 53.9 ft. to spike.