

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T24-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3296)</p> <p>-----</p> <p>Set Dogwood post 40" long, 5" dia., 18" in ground for the qr. sec. cor.on S. bdy. of sec. 32, from which A Fir 40" dia., bears S.89°E., 81 lks. dist. A Maple 10" dia., bears N.85°W., 17 lks. dist.</p>
<p>GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3305)</p> <p>-----</p> <p>(29.42 chs.) The old ¼ sec. cor. (found as described above) (40.00 chs.) (West) Set a post 3½ ft. long, 3" sq., 24" in the ground for ¼ sec. cor. on So. bdy. Sec. 32, mkd. ¼ S on N. face, from which A Hemlock 6" dia., bears N.27°E., 31 lks. dist. mkd. ¼ S BT A Hemlock 8" dia., bears S.34°W., 42 lks. dist. mkd. ¼ S BT.</p>
<p>GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3385)</p> <p>-----</p> <p>(At 29.42 and 41.45 chains), "No trace of old ¼ sec. cor. can be found after diligent search".</p>
<p>Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - March 6, 1975 - C.S. File 58/45</p> <p>-----</p> <p>Set 2" x 3 ft. Iron pipe 2 ft. in the ground with brass cap stamped S¼ S32. Referenced by: 12" Fir N.50°30'E., 56.1 ft. "W" nail, W. Co. tag reads: Sec.32 T24S R8W 56.1 ft. S.50°30'W. to S ¼ Cor., scribed ¼ S32 BT. 72" Fir N.30°W., 70.3 ft. "W" nail, W. Co. tag reads: Sec. 32 T24S R8W 70.3 ft. S.30°E. to S ¼ Cor., scribed ¼ S32 BT.</p>
<p>BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16433)</p> <p>-----</p> <p>(Cont. Next Page)</p>

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 243700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The $\frac{1}{4}$ sec. cor. of sec. 32 only, reestablished by proportionate measurement and recorded by Reppeto in 1975, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1 $\frac{1}{2}$ " dia., firmly set, projecting 8" above ground with brass cap mkd. S 1/4

S 32

from which the remains of bearing trees mkd. by Reppeto

A Fir snag 10" dia., bears N.50 $\frac{1}{2}$ °E., 85 lks. dist. with scribe marks $\frac{1}{4}$ S32 BT visible on open blaze.

A Fir 70" dia., bears N.30°W., 112 lks. dist. with scribe marks $\frac{1}{4}$ S32 BT visible on bark.

and a new bearing tree

A Fir 20" dia., bears N.40°E., 112 lks. dist., mkd. $\frac{1}{4}$ S32 BT.