

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3953)

Set yew ¼ post 3 ft. long & 3" sq. from which a
Hemlock, 16" dia., bears S.65°E., 10 lks.
Hemlock, 14" dia., bears S.15°W., 23 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3979)

Intersect the ¼ sec. cor. bet. secs. 32 & 33 which is a post, firmly set, marked & witnessed as described by Surveyor General.

H.R. Reppeto - For: Weyerhaeuser Co. - Oct. 1974 -C.S. ~~55/309~~
C.S.58/8-45 (File number corrected & dated added 7/16/2020)

Set - 1½" x 3' Gal. I. Pipe, with brass cap marked: T25S R8W
¼ Cor 32|33
BTs - A 28" Red cedar N.77°30'E. 29.0 ft. (H.D.) scribed ¼ S
BT & further marked with Weyerhaeuser tag and gal.
spike in root collar.
An 18" Red cedar N.76½°W., 54.0 ft. (H.D.) scribed ¼ S
BT and further marked with a Weyerhaeuser tag and
gal. spike in the root collar.

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15038)

The ¼ sec. cor. of secs. 32 & 33, monumented with an iron post, 1½" dia., firmly set, projecting 12" above ground, with brass cap mkd.
T 25 S
¼ 32 33
R 8 W
from which bearing trees of which I have no record
A cedar, 24" dia., bears N.73¾°E., 44 lks., with scribe marks ¼ S BT visible on open blaze.
A cedar, 15" dia., bears S.83°W., 82½ lks., with scribe marks ¼ S BT visible on open blaze.

Tony Hostetter - For: Weyerhaeuser Co. - Feb. 2018 - M174-25

Found - 1972 BLM Brass cap, from which:
28" Cedar stump, no marks, bears; N.74°E., 29.0 ft to center. (rec. N.73¾°E.)
18" Cedar snag, BT tag, bears; S.83°W., 54.5 ft to center. continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs- 4" Fir, marked "X" in bark, BT tag bears; N.60°E.,
16.2 ft to spike.
8" Fir, scribed "S32 ¼ BT", BT tag, bears; S.49°W.,
5.4 ft to spike