

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, & 33, only (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3953)

- 
- Set cedar post 4 ft. long 4" sq. from which a
  - Hemlock, 14" dia., bears S.10°W., 22 lks.
  - Hemlock, 18" dia., bears S.68°E., 45 lks.
  - Hemlock, 24" dia., bears N.50°W., 21 lks.
  - Hemlock, 10" dia., bears N.40°E., 17 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3979.)

-----

The cor. for secs. 28, 29, 32 and 33, was, badly decayed; otherwise marked & witnessed as described by the Surveyor General. I now change this cor. to refer to secs. 28 & 33 only, as follows: At the exact point, where old cor. stood., I set a new cedar post, 3 ft. long, 4" sq. 24" in the ground, for cor. of secs. 28 & 33, marked T25S S28 on NE., R8W S33 on SE., with 1 notch on S, & 3 notches on N edges; from which

- A fir, 24" dia. bears N.70°E. 47 lks. mkd: T25S R8W S28 BT
- A fir, 29" dia. bears S.80°E. 64 lks. mkd: T25S R8W S33 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Sept 1968 - C.S. File 54/72

-----

Found - No trace of orig. 1881 BTs.  
 24" now 30" Fir Snag, N.70°E. 31.0 ft., open & shows "BT" scribe, open higher & find "W S28" scribe.  
 29" now 36" Fir N.88°E. 42.4 ft., (Rec.S80°E). Open & find scribe.

Set - Brass Cap at Cor. Mkd: County Surveyors T25S R8W  
 Office  
 1968 CC | S 28  
 | S 33

New BTs- 12" Cedar S.69°E., 31.1 ft., mkd: T25S R8W S33 CS BT  
 10" Hemlock N.85°E. 21.2 ft. mkd: T25S R8W S28 CS BT

This corner lies on very steep northerly slope in shallow draw, & approx. 204 ft. N of CC Secs. 29 & 33, (rec. 198 ft.)

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15039)

-----

The cor. of secs. 28 & 33 only, perpetuated & rec'd by Tracy, in 1968, monumented with an iron post, 1" dia., firmly set, projecting 12", above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Wygant continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, & 33, only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir snag, 27" dia., bears N.70°E., 47 lks., with scribe marks W S28 visible on partially healed blaze.  
A fir, 34" dia., bears N.88°E., 61 lks., with scribe marks S R visible on partially healed blaze. (Rec., N.80°E., 64 lks.)  
and BTs mkd. by Tracy  
A root hole, bears N.85½° E., 32 lks., with a down hemlock alongside, 10" dia., no marks visible.  
A cedar, 10" dia., bears S.69°E., 48½ lks., with scribe marks T2SS R8W S33 CS BT visible on open blaze.

---

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Oct. 12, 1988 - C.S. File 62/59-5  
-----  
Found - 1968 County 2½" brass cap on a 1½" O.D. iron pipe that measures 36" long, is laying on top of ground, out of position. 1968  
24" now 27" dia. rotted 5 ft. high D.Fir stump with scribing visible on upper blaze "5 8 R8" bears N.70°E. 31.0 ft. (agrees with rec.) 1911 resurvey BT. A BT tag on stump with initials H.W.T. shows a bearing of N.82°W., 23 ft. Source unknown.  
29" now 39" dia. 4 ft. high D.Fir stump with illegible scribing visible in a previously opened upper blaze, bears N.88°E., 40.3' (Rec. N.88°E., 42.4 ft. is a slope measurement from 1968) Agrees well with 1972 resurvey.) 1911 resurvey BT.  
Set - Position of corner determined from two 1911 resurvey BTs at bearing & distances as found. Position is referenced & 1968 DCSO BC/IP with marks "RESET 1988" added is set. A 2 ft. dia. mound of sand stone is placed around BC. BC protrudes 4" above mound of sandstone.  
New BTs- 6" hemlock double blazed and scribed "T25S R8W S33 CS BT" bears S.70½°E., 49.2 ft.  
5" cedar double blazed & scribed "X BT" bears N.31°E., 50.6'  
Corner lies on a steep north slope at the west edge of a northerly running ravine, in a recently logged clear cut.

---

Fd. Ok 10/1994 - M119-41