

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION CC Secs. 20 & 29 (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4000)

-----  
Intersect the W. Bdy. of Sec. 28, 2.90 chs. S.0°04'E., from the cor. of sees. 21 & 28. At point of intersection, I set a cedar post, 3 ft. long, 4" sq. 24" in the ground, for closing cor. of secs. 20 & 29, marked C C T25S R8W on W., S29 S & S 20 on N faces; with 2 grooves on S. & 4 grooves on N. faces; from which  
A cedar, 30" dia. bears S.39°W. 21 lks mkd T25S R8W S29 BT  
A cedar, 20" dia. bears N.43°W. 39 lks mkd T25S R8W S20 BT

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15040)

-----  
The closing cor. of secs. 20 & 29, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.  
T25S R8W  
CC  $\frac{S\ 20}{S\ 29}$  S 28  
1972

from which  
A hemlock, 11" dia., bears S.37½°W., 183 lks., mkd. T25S R8W S29 CC BT.  
A hemlock, 17" dia., bears N.65¾°W., 245 lks., mkd. T25S R8W S20 BT.