

PRIMARY CORNER DESCRIPTION CC Secs. 21 & 28 (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3954)

Set hemlock post 4 ft. long & 4" sq. firmly in the ground from which

- A cedar, 16" dia., bears S.70°W., 23 lks.
- A hemlock, 24" dia., bears N.86°W., 89 lks.
- A cedar, 14" dia., bears S.60°E., 91 lks.
- A cedar, 18" dia., bears N.10°E., 100 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3980)

Find evidences of old cor. of sees. 21 end 28, 10 lks, W. Post destroyed; bearing trees badly decayed, otherwise marked & witnessed as described by the Surveyor General. Set new cedar post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 21 & 28, marked T25S S21 on NE., R8W S28 on SE., with 2 notches on S and 4 notches on N from which

- A fir, 48" dia. bears N.85°E. 56 lks. mkd: T25S R8W S21 BT
- A cedar, 15" dia. bears S.0°30'E. 84 lks. mkd: T25S R8W S28 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Oct. 1968 - C.S. File 54/72-37

Found - Orig. 48", now 60" Fir, alive, N.85°E. 37.0 ft., shows good scar.
Orig. 15", now 30" Cedar, alive, S.0°30'E. 55.4 ft., alive, open & find scribe "W".
Orig. 1881, 16", now 48" Cedar S.70°W. 18.5 ft. (Rec. 15.2) No scar fd.

Set - Brass Cap at Cor. Mkd: County Surveyors T25S R8W
Office | S 21
1968 | S 28

New BTs- 14" Hemlock S.61°E. 40.1 ft. mkd: T25W R8W S28 CS BT
11" Hemlock N.14°E. 22.5 ft. mkd: T25W R8W S21 CS BT
This corner lies 8 ft. N. of small dry ravine, course SW & 100 ft. East of Arrow Creek, course S.E. Best route to corner at this time is hike 1¾ mi. up Arrow Creek from logging road in Cedar Ck. Canyon. We put yellow line tag on log in Arrow Ck. about 100 west of corner.

continued next page

PRIMARY CORNER DESCRIPTION CC Secs. 21 & 28 (West)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15040-1)

The cor. of secs. 21 & 28 only, perpetuated & rec'd by Tracy, in 1968, monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which the remains of the original BTs

A cedar snag, 48" dia., bears S. 70° W., 28 lks., no marks visible. (Record, 23 lks.)

and bearing trees mkd. by Wygant

A fir, 60" dia., bears N.85°E., 56 lks. with healed blaze.

A cedar, 30" dia., bears S.0°30'E., 84 lks., with scribe mark W visible on partially healed blaze.

and bearing trees mkd. by Tracy

A hemlock, 12" dia., bears N.14°E., 34 lks., with scribe marks T25S R8W S21 CS BT, visible on open blaze

A hemlock, 14" dia., bears S.61°E., 60½ lks., with scribe marks T2SS R8W S28 CS BT, visible on open blaze.

Mark Smalley - for Weyerhaeuser Co. & Kenneth Ford - Oct. 1994 - M119-41

Found - 60" Fir, N.85°E., 37', healed stump

16" Hemlock, S.61°E., 40.1', part healed stump

Set - 5/8" x 28" Iron rod & aluminum cap marked "LS 2354"
6" below surface of dirt road at record bearing & dist. from fd. BT's.

7" fir, N.88°E., 27.1', scribed "S21 BT"

6" fir, N.36°E., 23.3', scribed "S21 BT"

8" fir, S.76°E., 36.2', scribed "S28 BT"

8" alder, S.18°W., 37.5', scribed "S COR BT"