

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION CC Secs. 17 & 20, East

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 4004)

Intersect the W. bdy. of sec. 21, 3.16 chs. S.3°40'W., from the cor. of seas. 16 and 21. At point of intersection, I set a fir post, 3 ft. long, 4" sq. 24" in the ground for closing cor. for seas. 17 and 20, marked C C T 25 S R 8 W on W., S 20 on S. and S 17 on N. face; with 3 grooves on N. and S. face; from which

A fir, 16" dia. bears S.80°W. 42 lks mkd: T25S R8W S20 BT
A fir, 16" dia. bears N.22°W. 13 lks. mkd: T25S R8W S17 BT

BLM dependent resurvey by James E. Jelley & Jack W. Bowder, Cadastral Surveyors, under Group #767, surveyed April/May 1972 - (DCSO records Vol. 36 Page(s) 15051-2)

True point for the closing cor. of secs. 17 & 20.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 25 S
CC S 17 S 21
S 20
R8W
1972

from which

A fir, 42" dia. bears S.15½°W. 40 lks. mkd. T25S R8W CC BT
A cedar, 6" dia., bears N.61°W., 24½° lks., mkd. T25S R8W S17 CC BT.

From this point, the original closing cor. of secs. 17 and 20, bears N.89°41'E., 0.14 chs., monumented by person(s) unknown with an iron pipe, ½" dia., firmly set, projecting 6" above ground, from which the remaining original bearing tree: A fir, 25" diam., bears N.22°W., 13 lks., with healed blaze. From this same point, the cor. of sees. 16 and 21 only, bears N.3°08'E., 3.16 chs.