

PRIMARY CORNER DESCRIPTION Cor. Secs. 8 & 17 only, East

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3987)

Set a cedar post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 8 & 17 marked T25S S17 on SW, R8W S8 on NW faces; with 4 notches on S & 2 notches on N edges; from which

A fir, 24" dia., bears S.39°30'W., 46 lks., mkd: T25S R8W S17 BT.

A fir, 30" dia. bears N.51°W., 58 lks. mkd: T25S R8W S8 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July/Aug 1968 - C.S. File 52/42-11

Found - Orig.24", now 38" Fir, down & decaying S.39½°W. 30.4 ft. no scribe.

Orig.30", now 48" Fir, alive, N.51°W. 38.3 ft. opened & shows scribe & reverse on pieces at base of BT.

Set - Brass Cap at Cor. mkd: County Surveyors T25S R8W
Office S 8
1968 S 17

New BTs- 15" Hemlock S.46°W. 21.3 ft. mkd. T25S R8W S17 CS BT
14" Hemlock N.69°W. 16.7 ft. mkd. T25S R8W S8 CS BT.

This corner lies on moderate W. slope 75' E. of old jeep trail. The Sec. Cot', to Secs.9 & 16 bears N. approx. 208 ft.

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16451)

The cor. of sees. 8 & 17 only, perpetuated & recorded by Tracy, in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 4" above ground, with brass cap, (properly) mkd.

from which the remains of the original bearing trees

A root hole, bears S.39½° W., 46 lks., with a down fir alongside, 40" diam., no marks visible.

A fir, 48" dia., bears N.51°W., 58 lks., with scribe marks S8 R8W visible in reverse and relief on overgrowth.

and bearing trees mkd. by Tracy

A hemlock, 15" dia. bears S.46½°W., 32 lks. with illegible scribe marks visible on partially healed blaze.

A hemlock, 12" dia., bears N.69½° W., 25 lks., with scribe marks T25S R8W S8 BT visible on open blaze.

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8 & 17 only, East

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Ronald L Rice - Nov. 2016 - Roseburg Resources Co - M172-77

Found - Douglas Co. brass cap dated 1968
48" metal capped D.Fir stump bears N.51°W., 38.3',
no scribing visible.
15" hemlock rotted stump bears S.46½°W., 21.1', no
marks.
12" hemlock rotted stub bears N.69½°W., 16.5', no
marks.
Brass cap at NW Cor Sec. 16 bears N.0°47'W., 194.66'
New - 13" D.Fir bears S.70°W., 8.3', blazed, scribed T25S
R8W S17 BT.
11" D.Fir bears N.62°W., 20.9', blazed, scribed T25S
R8W S8 BT.
Steel post adjacent to corner.