

PRIMARY CORNER DESCRIPTION Cor. Secs. 9 & 16 only, East

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3987)

Set a fir post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 9 & 16 marked T25S S19 on NE, R8W S168 on SE faces; with 4 notches on S & 4 notches on E edges; from which
 A fir, 48" dia. bears N.21°E., 77 lks. mkd: T25S R8W S9 BT
 A fir, 48" dia. bears S.89°E. 34 lks. mkd: T25S R8W S16 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July/Aug 1968 - C.S. File 52/42-10

Found - Orig. 48" Fir, now snag, N.21°E. 50.8 ft., scribe visible on unhealed blaze.
 Orig. 48" Fir, now snag, S.89°E. 22.4 ft., scribe visible on unhealed blaze.

Set - Brass Cap at Cor. mkd: County Surveyors T25S R8W
 Office S 9
 1968 S 16

New BTs- 8" Cedar S.68°E. 21.7 ft. mkd. T25S R8W S16 CS BT
 9" D.Fir N.59°E. 18.2 ft. mkd. T25S R8W S9 CS BT.

This corner lies on extremely steep N.E. slope 132 ft. N. of top of ridge. The Sec. Cor. to Secs. S & 17, bears S. about 208 ft.

Note - I feel these Orig. BTs. were snags when scribed.

BLM Dependent resurvey by James Jelley, Harvey Wofford Wayne Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page 16452)

The cor, of sees. 9 & 16 only, perpetuated & recorded by Tracy in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
 A fir snag, 40" dia. bears N.21°E. 68 lks. w/scribe marks T25S R8W S9 BT visible on opened blaze (Rec 77 lks)
 A fir snag, 44" dia., bears S.89°E., 34 lks., with scribe marks T25S R8W S16 BT visible on opened blaze.

and bearing trees mkd. by Tracy
 A fir, 12" dia., bears N.57½° E., 26 lks., with healed blaze.
 A cedar, 12" dia. bears S.69½°E. 33 lks. with scribe marks T25S R8W S16 BT visible on partially healed blaze.

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300503

PRIMARY CORNER DESCRIPTION Cor. Secs. 9 & 16 only, East

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald L Rice - Nov. 2016 - Roseburg Resources Co - M172-77

Found - Douglas Co. brass cap dated 1968
40" D.Fir snag bears N.21°E., 44.9', no marks.
44" D.Fir snag bears S.89°E. 22.4', scribing visible
Rec. 12" fir bearing N.57½°E., down out of position.
15" R.Cedar bears S.69½°E., 21.8', healed face.
Brass cap at NE Cor. Sec 17 bears S.0°47'E., 194.66'
New BT - 14" R.Cedar bears N.0½°E., 5.6', blazed, scribed
T24S R8W S9 BT.
Steel post adjacent to corner.