

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 8 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3989)

Set a fir post, 3 ft. long 4" sq. 24" in the ground, for ¼ sec. corner, for sec. 8 only, marked ¼ S8 on W face, from which:

A fir, 50" dia., bears S.5°W., 21 lks., mkd: ¼ S8 BT.

A fir stump, 60" dia., bears N.10°W., 24 lks. mkd: ¼ S8 BT

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16452-3)

The ¼ sec. cor. of sec. 8 only, determined at record bearing & distance from the only remaining original BT

A fir, 63" dia., bears S.5°W., 21 lks., with scribe mark 8 visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T25S R8W

¼|
S 8|
1979

from which a new bearing tree

A fir, 6" dia., bears N.58°W., 11 lks., mkd. ¼ S8 BT.