

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300543

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 9, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3989)

-----  
Set dogwood post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. for sec. 9 only marked ¼ S9 on E face, from which  
A fir, 45" dia., bears N.12°E., 34 lks., mkd: ¼ S9 BT.  
A fir, 36" dia., bears S.63°30'E., 63 lks., mkd: ¼ S9 BT.

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16453)

-----  
The ¼ sec. cor. of Sec. 9 only, determined at record bearing & distance from the remains of an original BT:

A root hole, bears N.12°E., 34 lks., with a down fir alongside, 62" dia., with scribe marks ¼ S9 BT visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T25S R8W

¼  
|  
S 9  
1979

from which new bearing trees

A fir, 9" dia., bears N.20¼°E., 8½ lks., mkd. ¼ S9 BT.  
A fir, 5" dia., bears S.8°E., 36 lks., mkd. X BT.