TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # .300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5 & 8 only, East

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3990)

---

Set a fir limb post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 5 & 8, marked T25S R8W on SW & R8W S5 on NW faces; with 5 notches on S & 1 notch on N edges; from which
A fir stub, 40" dia., bears N.10°W., 42 lks., mkd: T25S R8W S5 BT.
A fir, 80" dia. bears S.20°W., 14 lks. mkd: T25S R8W S8 BT

---

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Sept. 1967 - C.S. File 49/88-15

---

Found - Orig. 40" Fir, now snag, N.10° W. 27.7 ft., shows scribe on unhealed blaze.
Orig. SW BT, now down & slid downhill approx. 100 ft., shows scar.
Set - Brass Cap at Cor. mkd: County Surveyors T25S RS8W Office S 5 1967 S 8
New BTs- 8" Hemlock N.9½°W. 20.1 ft. mkd. T25S R8W S5 CS BT.
10" Hemlock S.48°W. 40.8 ft. mkd. T25S R8W S8 CS BT.
Note - This cor. lies on steep N. slope 208' S. of cor. secs. 4 & 9.

---

BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16453-4)

---

The cor. of secs. 5 & 8 only, perpetuated & recorded by Tracy in 1967, monumented with an iron post, 1½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree
A fir snag, 40" dia., bears N.10°W., 42 lks., with scribe marks S5 BT visible on opened blaze.
and bearing trees mkd. by Tracy
A hemlock, 14" dia., bears S.47½°W., 61 lks., with scribe marks R8W S8 CS visible on partially healed blaze.
A hemlock, 12" dia., bears N.9½°W., 30 lks., with scribe marks R8W S5 visible on partially healed blaze.