

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 5 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3992)

Set a fir limb post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. for sec. 5 only marked ¼ S5 on W face; from which
 A laurel, 14" dia., bears S.30°W., 34 lks., mkd: ¼ S5 BT.
 A fir, 30" dia., bears N.50°W., 19 lks., mkd: ¼ S5 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - July/Aug 1968 - C.S. File 54/72-9

Found - Remains of rock mound & decayed sq. post, from which
 Orig. 14" now 18" Laurel, alive, S.30°W., 22.4 ft. open & find scribe & reverse.
 Orig. 30" now 40" Fir, alive, N.50°W., 12.5 ft shows very good scar, we do not open.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T25S R8W OFFICE 1968 ¼ S 5|
New BT - 10" D.Fir S.2°W., 39.0 ft. mkd: "¼ S5 CS BT"
 Orig. 40" D.Fir N.50°W., 12.5 ft. bark scribed "¼ S5 CS BT" above scar.
This corner lies on very steep, rocky SW slope about 80 ft. S of top of rocky ridge, sloping SE.

BLM Dependent resurvey by James Jelley, Harvey Wofford, Wayne Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page 16455)

The ¼ sec. cor. of sec. 5 only, perpetuated & rec'd by Tracy in 1963, monumented with an iron post, 1½" dia. firmly set, projecting 6" above ground with brass cap (properly) mkd. from which the orig. BTs
 A madrone, 15" dia., bears S.30°W., 34 lks., with scribe marks ¼ S5 BT visible on opened blaze.
 A fir, 38" dia., bears N.50°W., 19 lks., with healed blaze, & scribe marks ¼ S5 CS BT visible on bark.
and BT mkd by Tracy
 A fir, 15" dia., bears S.2°W., 58 lks., with healed blaze.