

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 300643

PRIMARY CORNER DESCRIPTION West 1/4 Cor Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3992)

Set a fir post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. for sec. 4 only marked ¼ S4 on E face; from which
A fir, 22" dia., bears S.56°10'E., 71 lks., mkd: ¼ S4 BT.
A fir, 20" dia., bears N.89°50'E., 61 lks., mkd: ¼ S4 BT.

BLM Dependent resurvey by James Jelley, Harvey Wofford, Wayne Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page 16455-6)

Point for the ¼ sec. cor. of sec. 4 only, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

T25S R8W
 |
 | ¼
 | S 4
 |
 1979

from which

A sawed fir stump, 12" dia., bears N.62½°E., 27 lks., mkd: ¼ S4 BT.

A sawed fir stump, 48" dia., bears S.26°E., 37 lks., mkd: ¼ S4 BT.