

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 and 33 only, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3304)

Set a sandstone 22 x 8 x 6 ins., 16" in the ground for cor. to secs. 32 and 33, marked with 4 notches on E. and 2 notches on W. edges, from which

- A Fir 6" dia., bears N.73°E., 49 lks. dist. mkd. T24S R8W S33 BT.
- A Fir 48" dia., bears N.42°W., 91 lks. dist. mkd. T24S R8W S32 BT.
- A Fir 60" dia., bears S.60°E., 31 lks. dist. mkd. T24S R8W S32 and 33 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3385)

Cor. of secs. 4, 5, 32 and 33, which is a sandstone firmly set, mkd. and witnessed as described by the Surveyor General, bears S. 118 lks. dist. I destroy all marks referring to secs. 3 and 4 on Fir S.60°E., from cor.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13319-20)

The cor. of secs. 32 and 33 only, determined at record bearing and distance from the remaining original bearing trees:

- A Fir 60" dia., bears S.60°E., 31 lks. dist., bark scribed T24S R8W S32 & 33 BT.
- A Fir 48" dia., bears N.42°W., 91 lks. dist., bark scribed T24S R W S32. At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 24 S R 8 W
<u>S 32 S 33</u>
S 4
T 25 S R 8 W
1962

from which new bearing trees

- A Hemlock 24" dia., bears N.30°E., 149 lks. dist. mkd. T24S R8W S33 BT.
- A Fir 62" dia., bears N.16½°W., 133 lks. dist., bark scribed T24S R8W S32 BT.

(Cont. Next Page)

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 303700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Gary L. Langlitz, Deputy, Wit:
A. Vic Cangie; Jerry Jackson; Dennis Johnston - Jan. 6, 1976
- C.S. File 59/2-3

Found - An orig. 48" D.Fir in good condition, bark scribing
visible, bears N.42°W., 60.1 ft.
A 24" Hemlock, alive with scribing visible on
unhealed blaze, bears N.30°E., 98.3 ft. (1962)
A 62" D.Fir in good condition, bark scribing
destroyed by logging operations bears N.16½°W.,
87.8 ft. We rescribe on bare wood "T25S R8W S32
CS BT" on a single blaze.

We find the brass cap set in 1962 lying alongside a BT. We
reset the GLO monument in its proper position with respect to
the found bearing trees. This monument is mkd. as described
in the official record - we ADD the markings "CS 1976" to the
brass cap.

Corner is located on the E. bank of a small stream along an
E-W cutting line at the N. edge of a clearcut.

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L.
Rogers, Cadastral Surveyors, under Group #'s 926 and 958 -
Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s)
16431-32)

The Cor. of secs. 32 and 33 only, determined at record brg.
and distance from the remains of the original bearing trees:

A sawed Fir stump 60" dia., bears S.60°E., 31 lks. dist.
no marks visible.

A Fir 52" dia., bears N.42°W., 91 lks. dist. with scribe
marks T24S R8W S32 BT visible on bark.

and bearing trees mkd. by White and Beck:

A Hemlock 26" dia., bears N.30°E., 149 lks. dist., with
scribe marks T24S R8W S33 BT visible on open blaze.

A Fir 62" dia., bears N.16½°W., 133 lks. dist. with scribe
marks T24S R8W S32 BT visible on pitched over blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
with brass cap mkd:

T 24 S R 8 W

S 32 | S 33

S 4

T 25 S R 8 W

1979