

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3977-8)

Set a fir post, 3 ft. long, 4" sq. 24" in the ground, for ¼ sec. cor. Mkd: S16 on N and 21 on S face from which
A fir, 24" dia., bears N.24°30'E., 12 lks., mkd: ¼ S16 BT.
A fir, 16" dia., bears S.16°30'W., 37 lks., mkd: ¼ S21 BT.

David Edwards - For: Roseburg Resources Co. - 9/2020 - C.S. File 65/107-11

Set ¼ corner at proportionate position
Set - 5/8" dia. steel rebar with 2½" dia., alum. cap mkd as per the 2009 BLM manual and also mkd: "ROSEBURG RESOURCES CO" and LS 2339" and "2021"
A 9" Fir scribed "¼ S16 BT" bears N.63°E., 13.7'
A 40" dia. Fir w/WEYCO tag bears S.28°42'W., 13.1'.
6 ft. steel post 2' East