

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION W.C. 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3991)

Set a fir limb post, 3 ft. long, 4" sq. 24" in the ground, for 1/4 sec. cor., marked 1/4 S4 on N & 9 on S face; from which
A fir, 32" dia., bears S.33°30'E., 80 lks., mkd: 1/4 S9 BT.
A fir, 36" dia., bears N.52°30'E., 156 lks., mkd: 1/4 S4 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & crew - Sept. 1967 - C.S. File 49/88-16

Witness Corner to Corner to Sections 4 and 9. - 36
Found - Orig. 32", now 32" Fir Snag, S.33 1/2°E. 52.8 ft., scribe visible on unhealed blaze.
Since the exact corner point falls on logs in creek, we move 3.0 ft. North & 3' S to corner.
Set- Brass cap at Cor. mkd: County Surveyors T25S R8W
Office, 1967 Wit Cor. 1/4 $\frac{S\ 4}{S\ 9}$

New BTs- 7' D.Fir S.43°E., 9.3 ft. mkd. WC 1/4 S9 CS BT.
9" D.Fir N.87°W. 36.4 ft. mkd. WC 1/4 S4 CS BT.
Note - This Wit. Corner lies in flat along creek bottom.
No trace other BT