TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3948-9)

Set yew ¼ post 3 ft. long & 3" sq. from which a
Fir, 40" dia., bears S.70°W., 32 lks.
Fir, 36" dia., bears N.62°E., 43 lks.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Sept 1968 - C.S. File 54/72-24

Found - Orig. 36" now 60" Fir, alive, N.62°E., 28.4 ft., fragmentary bark scribe & axe notch. "W" nail & tag.
No trace of other orig. BT due to slide.
Weyerhaeuser method BTs as follows (unrecorded)
16" hemlock S.47°E., 31.4 ft. "W" nail & tag.
16" cedar S.62°W., 41.0 ft. "W" nail & tag.
Set - Brass cap at cor. mkd: County Surveyors T25S R8W Office 1968 ¼ S33|S 34
New BTs- 13" Hemlock N.39°E., 6.4 ft. mkd: ¼ S34 CS BT.
15" Hemlock S.8°W., 11.3 ft. mkd: ¼ S33 CS BT.
This corner lies in old slide sloping westerly. Orig. BT fd. lies on NE edge of slide on top of bank & appears not to have moved.