

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated  
May 26, 1881 (DCSO records Vol. 9 Page(s) 3950)

-----  
Set post 4 ft. long & 4" sq. from which  
Fir, 30" dia., bears N.35°E., 18 lks.  
Dogwood, 10" dia., bears S.15°E., 24 lks.  
Hemlock, 20" dia., bears S.65°W., 66 lks.  
Fir, 36" dia., bears N.45°E., 39 lks.

Craig Templin - For: Weyerhaeuser Co. - Oct. 15, 1970 - C.S.  
File 55/177

-----  
Set - 1½"x3' iron pipe with brass cap mkd: T25S R8W  
12" Hemlock N.53°E., 69.1 ft. 21|22  
mkd: S22 T25S R8W BT. 28|27  
10" Hemlock N.69°W., 47.4 ft. 1970  
mkd: S21 T25S R8W BT.  
8" Hemlock S.66°E., 22.5 ft. (mkd: S27 T25S R8W BT)  
12" Fir S.86°W., 17.4 ft. (mkd: S28 T25S R8W BT)

Mark Smalley - Kenneth Ford & Weyerhaeuser Co. - Oct. 1994 -  
M119-41

-----  
Set - Brass plug mkd. "LS 2354" in rock at record bearing  
& distance from fd. BT's.  
Fd. - 10" hemlock, N.69°W., 47.4' stump  
12" hemlock, N.53°E., 69.1' rotten stump  
12" fir, S.86°W., 17.4' stob  
New - 5" fir, N.41°E., 53.2' "S 22 BT" (brg. & dist. to  
center of root crown, pistol butted)  
5" maple, S.81°W., 29.7' "S 28 BT"  
5" chinquapin, S.19°W., 38.1' "S 28 BT"  
15" hemlock, S.36°W., 22.3' "S 28 BT"