

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor Secs 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3951)

Set fir post 4 ft. long & 4" sq. from which a
Hemlock, 20" dia., bears S.10°W., 23 lks.
Fir, 8" dia., bears S.12°E., 52 lks.
Fir, 30" dia., bears N.70°E., 12 lks.
Fir, 16" dia., bears N.28°W., 13 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3976-7)

Set a fir post 3 ft. long 4" sq. 24" in the ground for cor. of secs. 15, 16, 21, & 22 marked T25S S15 on NE, R8W S22 on SE, S21 on SW, & S16 on NW faces with 3 notches on S & 3 notches on E edges; from which
A burnt fir, 50" dia., bears N.33°15'E., 122 lks., mkd: T25S R8W S15 BT.
A burnt fir, 40" dia., bears S.27°30'E., 77 lks., mkd: T25S R8W S22 BT.
A burnt fir, 50" dia., bears S.53°W., 102 lks., mkd: T25S R8W S21 BT.
A burnt fir, 50" dia., bears N.38°W., 84 lks., mkd: T25S R8W S16 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - Clete Putnam - Oct. 18, 1960 - C.S. File 49/88-6

Found - All 4 orig. BTs.
Orig. 50" now 60" Fir S.53°W., 67.3 ft., shows scars. I do not open.
Orig. 40" now 40" Fir snag S.27½°E., 50.8 ft., shows good scribe marks.
Orig. 50" now 50" Fir snag N.33°15'E., 80.5 ft. rotted, no scribing.
Orig. 50" now 50" fir snag N.38°W., 55.4 ft., shows good scribing.
Fd. very old scribed stake at corner.

Set - Brass cap at corner mkd: County Surveyors S 16|S 15
Office 1960 S 21|S 22

New BTs- 7" R.Fir bears N.45°W., 15.1 ft., scribed S16 T25S R8W CS BT.
10" R.Fir bears S.23°W., 20.8 ft., scribed S21 T25S R8W CS BT.
12" R.Fir bears N.11°E., 18.2 ft., scribed S15 T25S R8W CS BT.

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor Secs 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>8" R.Fir bears S.52°E., 35.2 ft., scribed S22 T25S R8W CS BT.</p>
<p>Fd. & used on BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13779-80) {Add the marks BLM 1965 to top of brass cap}</p>
<p>BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18865-6)</p> <p>-----</p> <p>The cor. of secs. 15, 16, 21 & 22, monumented with an iron post, 1" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees</p> <ul style="list-style-type: none">A rotted fir snag, 45 diam., bears N.33¼°E., 119 lks., no marks remaining.A rotted fir stump, size indeterminate, bears S.19°E., 79 lks., no marks remaining.A rotted fir stump, 64" dia., bears S.53°W., 102 lks., no marks remaining on rotted open blaze.A rotted fir snag, 30" dia., bears N.38°W., 86 lks., no marks remaining. <p>and bearing trees mkd. by Byron, in 1960</p> <ul style="list-style-type: none">A fir, 22" dia. bears N.10½°E., 27½ lks. with healed blazeA fir, 18" dia. bears S.52°E., 53½ lks., with healed blazeA fir, 15" dia. bears S.23°W., 31½ lks., with healed blazeA fir, 10" dia., bears N.48½°W., 23 lks. with healed blaze
<p>David Edwards - For: Roseburg Resources Co. - 9/2020 - C.S. File 65/107-11</p> <p>-----</p> <p>Found - 1960 County Surveyors brass cap</p> <ul style="list-style-type: none">27" Fir N.10½°E., 18.2'23" Fir S.52°E., 35.3'15" Fir snag S.23°W., 20.8'10" Fir snag N.48½°W., 15.2' <p>All with healed blaze.</p> <p>Set - 6 ft steel post 2' West.</p>
<p>2</p>