

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3952)

Set fir ¼ sec. post 3 ft. long & 3" sq. from which a
Laurel, 12" dia., bears N.50°E., 2 lks.
Fir, 7" dia., bears S.25°W., 16 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3976)

Set a Laurel post 3 ft. long 4" sq. 24" in the ground for ¼ sec. cor. bet. secs. 15 & 16 marked ¼ S16 on W & 15 on E face from which

A fir, 16" dia., bears S.7°30'E., 54 lks., mkd: ¼ S15 BT.
A fir, 16" dia., bears S.15°30'W., 55 lks., mkd: ¼ S16 BT.
This cor. falls on the old blazed line of survey. No trace of old ¼ sec. cor. (See Method of Procedure)

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18866-7)

Point for the ¼ sec. cor. of secs. 15 & 16, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

T25S R8W
¼
S 16|S 15
1989

from which

A fir, 13" dia., bears N.28°E., 21½ lks., mkd. ¼ S15 BT.
A fir, 8" dia., bears S.24°W., 18 lks., mkd. ¼ S16 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point unofficially established by a BLM administrative survey in 1970, record held at Roseburg District Office, bears N.36°W., 0.046 chs., monumented with an iron pipe, ¾" dia., projecting 18" above ground.