

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor Secs 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3952)  
-----  
Set a fir post 4 ft. long & 5" sq. from which a  
    Fir, 10" dia., bears N.50°W., 9 lks.  
    Dogwood, 6" dia., bears N.80°E., 14 lks.  
    Fir, 30" dia., bears S.45°W., 53 lks.  
    Fir, 20" dia., bears S.70°E., 21 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3971-2)  
-----  
At the cor. of secs. 9, 10, 15, & 16, which is an old post, badly decayed, but markings plain; fd BTs as described by the Surveyor General, but all are badly decayed & burnt. I reestablished this cor. as follows:  
At the exact cor. point where old cor. stood, I set a cedar post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 9, 10, 15, & 16, mkd T25S R10 on NE, R8W S15 on SE, S16 on SW & S9 on NW faces, with 4 notches on S & 3 notches on E edges from which  
    A fir, 36" dia., bears N.12°30'E., 83 lks., mkd: T25S R8W S10 BT.  
    A fir, 12" dia. bears S.20°E. 32 lks. mkd: T25S R8W S15 BT  
    A fir, 36" dia. bears S.45°W. 53 lks. mkd: T25S R8W S16 BT  
    A fir stub, 30" dia., bears N.9°30'W., 96 lks., mkd: T25S R8W S9 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - Clete Putnam - Oct. 18, 1960 - C.S. File 49/88-5  
-----  
Found - Orig. 30" now 48" Fir stump S.45°W., 35.0 ft. I open & find good scribing "BT"  
        Also find SE BT as recorded 1911 survey.  
Set brass cap at corner mkd: COUNTY SURVEYORS   S 9|S 10  
  OFFICE 1960       S 16|S 15  
New BTs- 20" R.Fir bears S.18°E., 19.2 ft., scribed S15 T25S R8W CS BT.  
        7" Maple bears N.70°E., 25.5 ft., scribed S10 CS BT (scribed high)  
        10" Hemlock bears N.43°W., 71.0 ft. scribed S9 T25S R8W CS BT.  
        7" R.Fir bears S.25°W., 24.6 ft., scribed S16 T25S R8W CS BT.

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd & used on BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16446-7)

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18867-8)

-----  
The cor. of secs. 9, 10, 15 & 16, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A sawed fir stump, 42" dia., bears S.45°W., 53 lks., with scribe marks 8W S16 BT visible on rotted blaze.  
and the remains of bearing trees mkd. by Wygant  
A sawed fir stump, 40" dia., bears N.12½°E., 83 lks., with illegible scribe marks on rotted blaze.  
A fir, 27" dia., bears S.20°E., 29 lks. with healed blaze.  
and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1960  
A sawed maple stump, 15" dia., bears N.70°E., 39 lks., no visible marks.  
A fir, 10" dia., bears S.25°W., 37 lks. with healed blaze.  
A hemlock, 20" dia., bears N.43°W., 107 lks., with healed blaze.  
No suitable trees available within limits in sec. 10.  
The corner is located at the SW. corner of a clearcut logging area.