

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3982-3)

Set yew post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 3, 4, 9 & 10 marked T25S S3 on NE, R8W S10 on SE, S9 on SW & S4 on NW faces; with 5 notches on S & 3 notches on E edges; from which

- A fir, 18" dia. bears N.75°E., 65 lks. mkd: T25S R8W S3 BT
- A fir, 18" dia. bears S.5°E., 51 lks. mkd: T25S R8W S10 BT
- A fir, 36" dia. bears S.41°W., 23 lks. mkd: T25S R8W S9 BT
- A fir, 36" dia. bears N.35°W., 70 lks. mkd: T25S R8W S4 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Dick West - July 1967 - C.S. File 49/88-12

Found - Orig. 18" now 20" Fir, turned out, N.75°E., 42.9 ft., we open & find "S 8 W BT" scribe on burned face.

Orig. 18" now 24" fir, alive, S.5°E., 33.7 ft., shows good scars.

Orig. 36" now 44" Fir, alive, S.41°W., 15.2 ft. shows good scar. Rescribe "T2S R8W S9 CS BT"

Orig. NW BT is down & out of place.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T25S R8W
OFFICE S 4 | S 3
1967 S 9 | S 10

New BTs- 10" D.Fir N.81°E., 52.7 ft., mkd: T25S R8W S3 CS BT.

48" D.Fir N.65°W., 44.2 ft., mkd: T25S R8W S4 CS BT.

Note - This corner lies on SE slope approx. 460 ft. N of Little Wolf Creek. This area has timber in the 30"-50" size.

Fd. & used on BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16449)