

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3985)

-----  
At point of intersection (1.69 chs. S.89°09'W of the cor. 33 & 34), I SET a Maple post 3 ft. long, 4" sq., 24" in the ground, for closing cor. for secs. 3 and 4, marked C C T25S R8W on S.; S3 on E.; and S4 on W. faces, with 3 grooves on E. and 3 grooves on W. faces; from which

A Fir 42" dia., bears S.40°30'E., 76 lks. dist. mkd. T25S R8W S3 BT.

A Fir 14" dia., bears S.68°W., 31 lks. dist. mkd. T25S R8W S4 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - May 14, 1958 - C.S. File 49/88-2

-----  
Found - Orig. 42" now 60" Fir, shows good scar. I do not open to face, S.40½°E., 50.2 ft.

Orig. 14" now 18" snag, I open and find good scribing "T25S R8W S3"

Set Brass cap at cor. mkd: County Surveyors Office

T 24 S  
S 33  
-----  
C C S4 | S3  
T 25 S R 8 W  
1958

New BTs- 10" Hemlock bears S.33°E., 17.0 ft. scribed CC S3 T25S R8W CS BT.

7" Hemlock bears S.4°W., 40.0 ft. scribed CC S4 T25S R8W CS BT.

A.R. Evans' stake for 33|34 bears S.35°E., 46.2 ft. I destroy his BTs. Evans used SE. BT of closing cor. for 3 & 4 for SE. BT 33 and 34.

Fd. and used in BLM Resurvey by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12608-09)

Fd. and used in BLM resurvey by C. Albert White; , Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13319)