

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3951)

Set fir 1/4 post 3 ft. long 3" sq. from which a
Cedar, 30" dia., bears S.55°E., 50 lks.
Fir, 36" dia., bears N.20°E., 14 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13779)

Point for the 1/4 sec. cor. of secs. 15 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2 1/2" dia., 24" in the ground with brass cap marked:
T25S R8W
1/4 S 15
S 22
1965

from which
A fir, 20" dia., bears N.10 3/4°E., 83 lks., mkd: 1/4 S15 BT.
A hemlock, 23" dia., bears S.42 1/4°E., 18 lks. mkd: 1/4 S22 BT

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18877-8)

The 1/4 sec. cor. of secs. 15 & 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap (properly) mkd.
from which the remains of BTs mkd. by Beck and Jelley
A root hole, bears N.10 3/4°E., 83 lks., with a down fir alongside, 24" dia., with healed blaze.
A hemlock, 26" dia., bears S.43 1/2°E., 18 lks., with healed blaze. (Record, S.42 1/4°E.)
and a new bearing tree
A fir, 14" dia., bears N.20°E., 63 lks., mkd. 1/4 S15 BT.

Fd. Ok by Ron Quimby, 6/1994 - M120-17

Tony Hostetter - For: Weyerhaeuser Co. - 1/25/2023 - C.S. file 65/111-45

Found - 1965 BLM brass cap (Vol. 50, Pg 18877-8)
22" Fir, face evident, BT TAG, bears; N.18°11'E., 41.3 ft to center. (Rec. N.20°E., 41.58')
26" Hemlock stump, scribing visible, bears; S.37°12'E., 11.4 ft to center. (Rec. S.43 1/2°E., 11.88')
Continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs- 36" Cedar, marked "X", BT tag, bears; N.65°53'E.,
6.7 ft to 6" spike, below "X".
10" Fir, marked "X", BT tag, bears; S.41°09'W., 14.8
ft to 6" spike, below "X"
54" Fir, marked "X", BT tag, bears; N.48°00'E., 10.6
ft to 6" spike, below "X".