

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3952-3)

-----  
Set fir ¼ sec. post 3 ft. long & 3" sq., from which a  
Fir, 14" dia., bears S.5°E., 15 lks.  
Fir, 24" dia., bears N.40°E., 20 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3972)

-----  
Set a fir post 3 ft. long 3" sq. 24" in the ground for ¼ sec. cor. marked ¼ S10 on N & 15 on S from which  
A burnt fir, 30" dia., bears N. 3 lks. mkd: ¼ S10 BT.  
A burnt fir, 10" dia. bears S.10°W., 21 lks. mkd: ¼ S15 BT  
No trace of old ¼ sec. cor. (See Method of Procedure)

BLM Dependent resurvey by James Jelley, Harvey Wofford Wayne Rogers, Cadastral Surveyors under Group # 926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol 42 Pgs 16445-6)

-----  
The ¼ cor. of secs. 10 & 15, reestablished by Roseburg Lumber Co. in 1963, at proportionate dist. & is accepted as the best available evidence of the position of the orig. corner, monumented w/iron pipe, 1" dia. firmly set, projecting 10" above ground.

At corner point - Set an iron post, 28" long, 2½" dia., 24" in the ground, directly over iron pipe, with brass cap mkd:

T25S R8W  
¼  $\frac{S\ 10}{S\ 15}$

1979 from which  
A fir, 12" dia., bears N.59°W., 18 lks., mkd: ¼ S10 BT.  
A fir, 10" dia., bears S.19°W., 43 lks., mkd: ¼ S15 BT.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18868-9)

-----  
The ¼ sec. cor. of secs. 10 & 15, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of BTs. by Jelley, Wofford, and Rogers  
A fir, 13" dia., bears S.19°W., 43 lks. with healed blaze.  
A sawed fir stump, 12" dia., bears N.59°W., 18 lks., with healed blaze.

No suitable trees available within limits in sec. 10.