

TOWNSHIP 25 RANGE 8 POINT IDENTIFIER # 440520

PRIMARY CORNER DESCRIPTION CS 1/16 S10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Les Roberts - Roberts Surveying Inc. For International Paper Company - 12/15/1986 - M103-37

Set - 5/8" x 30" Aluminum rod and cap (purple M.M buried under 30" rod.)
8" Fir, N.01°E. 30.2 ft. scribed/painted red.
16" Fir, N.75°W.27.3 ft. scribed/painted red.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18869

The center S 1/16 sec. cor. of sec. 10, established by Roberts, in 1986, and accepted as the corner; monumented with an aluminum rod, 5/8" dia., projecting 6" above ground, with aluminum cap mkd. I P TIMBERLANDS OPERATING CO
RLS 1039
CS 1/16*COR
1986
T 25 S R 8 W
from which bearing trees mkd. by Roberts
A fir, 10" dia., bears N.1°E., 46 lks., with healed blaze.
A fir, 18" dia., bears N.75°W., 41 lks. with healed blaze.
The corner is located at the S.E. corner of clearcut logging area, edge bears N. And W.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaese and Jeff Lorsung - 3/11/2026 - C.S. File 67/62-20

Found - 3/4" Alum. Cap on 5/8" iron rod proj. 6".
20" D. Fir N.1°E. 30.2 ft. (Rec. 46 lks)
New - Alum. Post with property line and land survey monument signs attached. The base bears N.85°W. 1.8 ft.
Notes - Mon. on north edge of small swamp in older reprod approx. 105 ft. west of gravel road.
Compass decl. 14 1/4°E.
TRIMBLE GEO XT POSITION
43°.40675562 N. 123°.63398175 W.