

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 440540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Secs. 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Les Roberts - For: International Paper Co. - Dec. 15, 1987 - M103-37 & C.S. File 63/46-2(H)

Set - 5/8" x 30" iron rod with alum. cap.
20" Fir bears S.36°W., 11.7 ft. Scribed/Washer/Painted.
22" Fir bears S.77°E., 8.5 ft. Scribed/Washer/Painted.
Set fence post with land survey monument sign wired to, beside alum. cap. Corner lies on south slope about 340 ft. South of ridge. Ridge bears S.70°W., & N.70°E.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18869-70)

The center ¼ sec. cor. of sec. 10, established by Les Roberts, in 1986, and accepted as the corner; monumented with an aluminum rod, 5/8" dia., projecting 3" above ground, with aluminum cap mkd.

I.P. TIMBERLANDS OPERATING CO.

RLS 1039

S 10

C¼ -|- COR

1986

T 25 S R 8 W

from which bearing trees mkd. by Roberts

A fir, 22" dia., bears S.77°E., 13 lks., with healed blaze

A fir, 22" dia., bears S.36°W., 19 lks., with healed blaze

From this point, the BLM Geodetic Control Station No. EC 41008 at latitude 43°24'25.886"N., longitude 123°37'34.279"W. (NAD 1927), determined by the NAVSTAR GPS, bears S.54°57'30" E., 32.270 chs., monumented with an aluminum tablet, 3" dia., set in cement, flush with the ground, mkd. EC 41008 GPS 1989.