

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3983)

Set a fir post 3 ft. long 4" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S3 on N & 10 on S face, from which

- A burnt fir stub, 20" dia., bears S.71°E., 7 lks., mkd: 1/4 S10 BT.
- A burnt fir stub, 20" dia., bears N.88°E., 156 lks., mkd: 1/4 S3 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - Sept 1967 - C.S. File 49/88-19

Found - Orig. 20" burnt Fir Stub, very badly decayed. S.71°E., 4.6 ft., blazed & very poor scribe "1/4 U" visible.

Orig. burnt Fir Stub, badly decayed, N.88°E., 101.0 ft. (Record 103.0 ft. No scribe found.)

Set - Brass Cap at Cor. mkd: COUNTY SURVEYORS T25S R8W
Office 1/4 S 3
1967 S 10

New BTs- 16" D.Fir S.27° E. 6.1 ft. mkd. 1/4 S10 CS BT.
8" D.Fir N.33°W., 6.7 ft. mkd. 1/4 S3 CS BT.

Note - This corner lies on very steep, north slopes, approx. 150 ft. south of Little Wolf Creek.

BLM Dependent resurvey by James Jelley, Harvey Wofford, Wayne Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page 16450)

The 1/4 sec. cor. of secs. 3 & 10, perpetuated and recorded by Tracy, in 1967, monumented with an iron post, 1 1/2" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd:

from which the remains of the original bearing trees

- A fir stump, size indeterminate, bears N.88°E., 156 lks., no marks visible.
- A root hole, bears S.71°E., 7 lks., with a down fir alongside, size indeterminate, no marks visible.

and the remains of bearing trees mid, by Tracy

- A fir snag, 8" dia., bears N.33°W., 10 lks., with scribe marks 1/4 S3 CS BT visible on open blaze.
- A fir, 18" dia., bears S.27°E., 9 1/2 lks., with healed blaze and a new bearing tree
- A fir, 6", dia., bears N.48 1/2°W.; 23 lks., mks. 1/4 S3 BT.