

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 441700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34, T24-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3295)

Marked a mountain Balm 5" dia. for the qr. sec. cor. on S. bdy. of sec. 34, from which
A Laurel 5" dia., bears S.45°W., 23 lks. dist.
A Fir 40" dia., bears N.88°W., 98 lks. dist.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3384)

Find no trace of old ¼ sec. cor., after diligent search.

BLM Resurvey by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12607)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 24 S R 8 W
¼ S 34
1959

from which
A W.Fir 13" dia., bears N.69½°E., 69 lks. dist. mkd. ¼ S34 BT.
A Madrone 18" dia., bears N.5°W., 57 lks. dist. mkd. ¼ S34 BT.

NOTE: Brass cap removed for road construction. Gary Langlitz, Douglas Co. Surveyors Office. Jan. 16, 1974

Douglas Co. Surveyors Office - Clell Goodwin, Deputy - Lenora Ladig, crew - Wit: Gary Heichel; Melvin Dunlop, Road Dept. - Jan. 6, 1976 - C.S. File 59/2-4

Found - An orig. 13" now 19" W.Fir, bears N.64°E., 45.5 ft. (Call N.69½°E., 45.5 ft.) alive and well healed.
An orig. 18" now 21" Madrone, bears N.5°W., 37.6 ft., alive and healed.

As the corner now falls on a steep, loose cut bank, we go on line N.88°42'W., 55.0 ft. and SET a Wit. Corner. At this point, WE SET a 2" x 30" I.P. with brass cap stamped:
(Cont. Next Page)

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 441700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34, T24-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyor 1976
T 24 S R 8 W
1/4 WC →
S 34

New BTs- 9" Fir with an axed "X" breast high and CSBT appearing in two lower blazes, bears N.35°W., 20.2 ft.
19" Fir with an axed "X" breast heigh and CSBT scribed in two lower blazes, bears N.26½°E., 40.5 ft.

We leave the original BTs intact.