

TOWNSHIP 25 RANGE 8 POINT IDENTIFIER # 460440

PRIMARY CORNER DESCRIPTION CE 1/16 S 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18880-81)

Point for the center E 1/16 sec. cor. of sec. 15.
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

E 1/16
C ----- C
S 15
1989

from which

A fir, 23 ins. diam., bears S. 58° E., 10 lks. dist., mkd. CE 1/16 S15 BT.

A fir, 15 ins. diam., bears N. 27½° W., 71 lks. dist., mkd. CE 1/16 S15 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point unofficially established by a Bureau of Land Management administrative survey in 1970, record held at Roseburg District Office, bears N. 82° 24' E., 0.015 chs. dist., monumented with an iron pipe, ¾ in. diam., projecting 10 ins. above ground.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 3/25/2026 - C.S. File 67/62-32

Found - ¾" BLM brass cap flush with surface.

E 1/16
C ----- C
S 15
1989

26" X 5 ft. rotted fir stump S.58°E. 6.6 ft. fully healed single blaze.

16" x 6 ft. rotted fir stump N.27½°W. 46.9 ft. fully healed single blaze.

¾" iron pipe N.82½°E. 1.0 ft. set by unofficial BLM administrative survey in 1970.

New - ⅝" x 30" iron rod with D.C.S.O. plastic cap. N.46°W. 34.6 ft. set proj. 6" in road cut bank.

Notes - Mon. in younger fir plantation approx. 25 ft. east and 35 ft. south of gravel road.

Compass decl. 14¼°E.

TRIMBLE GEO XT POSITION

43°.39646078 N. 123°.62953005 W.