

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3942)

-----  
Cor. to secs. 34, 35, 26, & 27  
Set maple post 4 ft. long 4" sq. from which  
A fir, 30" dia., bears S.50°E., 12 lks.  
A fir, 24" dia., bears S.20°W., 66 lks.  
A fir, 24" dia., bears N.50°W., 18 lks.  
A fir, 36" dia., bears N.10°E., 30 lks.

-----  
Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April 1968 - C.S. File 52/72-1

-----  
Found - Mound of stone & orig. BTs as follows:  
Orig. 30" now 36" fir snag, S.30°E., 7.9 ft. (rec. S.50°E.) shows old bark scribe in poor condition.  
Orig. 24" now 36" fir, S.40°W., (rec. S.20°W.) 43.6 ft., down bark scribe visible on underside.  
Orig. 24" now 32" fir, alive, N.30°W. (rec. N.50°W.) 11.9 ft., shows fair bark scribe.  
Orig. 36", now 48" fir, alive N.30°E. (rec. N.10°E.) 19.8 ft., old axe blaze & possible fragmentary bark scribe.

Note - All bearings off 20° as though Flint did not use any variation.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T25S R8W  
OFFICE S 27 | S 26  
1968 S 34 | S 35

New BTs- 14" Hemlock S.68°W. 30.2 ft. mkd: T25S R8W S34 CS BT  
14" Hemlock N.88°W. 42.5 ft. mkd: T25S R8W S27 CS BT  
14" Hemlock S.75°E. 10.3 ft. mkd: T25S R8W S35 CS BT  
12" Hemlock N.60°E. 33.7 ft. mkd: T25S R8W S26 CS BT