

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3943)

-----  
Set fir ¼ post 3 ft. long & 3" sq. from which  
A fir, 36" dia., bears N.80°W., 52 lks.  
A fir, 36" dia., bears N.45°E., 16 lks.

H.R. Reppeto - Weyerhaeuser Co. - 8/31/1973 - C.S. 55/309-2

-----  
After a thorough search of surrounding area, set a brass cap on a two inch pipe (single prop. meas.) from which:  
18" hemlock bears N.70°E., 21.0 ft. (WEYCO tag, "W" nail, scribed)  
30" Cedar bears N.85½°W., 29.4 ft., (WEYCO tag, "W" nail, scribed)  
Bearings were taken to the "W" nail & distances were measured to the center of the tree.

FD. brass cap & 2 BTs by D. Edwards M145-60 - Oct. 2004

Ron Quimby - 4/2017 June 2017 - C.S. File 65/95-32

-----  
Found - 2" IP with cap  
42" Cedar stump N.85½°W., 29.4 ft.  
24" Down Hemlock N.70°E., 21.0 ft.  
New - 12" Fir N.35°E., 40.0 ft. scribed ¼ S26 BT.  
12" Fir S.47°E., 7.2 ft. scribed ¼ S26 BT.  
20" Fir S.33°W., 9.1 ft. scribed ¼ S27 BT.  
18" Fir N.22°W., 26.4 ft. scribed ¼ S27 BT.  
Compass decl. 15½°E.