

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3945)

Set fir ¼ sec. post 3 ft. long & 3" sq. from which a
Fir, 20" dia., bears N.67°E., 10 lks.
Fir, 18" dia., bears S.80°W., 15 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13773)

The ¼ sec. cor. of secs. 22 & 23, determined at record bearing from the remains of the orig. BTs:

A fir, 30" dia., bears N.67°E., 12 lks., 10 lks. to face, mkd: ¼ S on a bark blaze. (Rec. 10 lks.)

A fir snag, 18" dia., bears S.80°W., 17 lks., 15 lks. to face, no marks visible on opened blaze. (Rec. 15 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap marked:

T25S R8W
 ¼
 S 22|S 23
 1965

from which new BTs

A fir, 15" dia., bears N.38°E., 24 lks., mkd: ¼ S23 BT.

A fir, 12" dia., bears N.15½°W., 48½ lks., mkd: ¼ S22 BT.

Fd. Ok 6/1994 - By Quimby - M120-17

BLM Dependent resurvey by Timothy J Moore, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2300 surveyed May 2006- (DCSO records BLM Plat 2011-1 & Vol. 57 Page(s) 22687)

The ¼ sec. cor. of secs. 22 and 23, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A sawed fir stump. 34" dia., bears N.67°E., 7.9 ft., with no marks visible.

and the remains of a bearing tree mkd. by Beck and Jelley

A decayed fir stump, size indeterminate, bears N.38°E., 15.8 ft., with no marks visible.

and new bearing trees

A fir, 7" dia., bears N.79½°E., 28.4 ft., mkd. ¼ S23 BT.

A fir, 21" dia., bears S.25¼°W., 9.5 ft., mkd. ¼ S22 BT.