

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3945)

Cor. to secs. 14, 15, 22, & 23
Set a cedar post 4 ft. long 4" sq. from which a
W.Fir, 16" dia., bears S.25°W., 43 lks.
Maple, 30" dia., bears N.63°W., 30 lks.
Alder, 16" dia., bears S.35°E., 50 lks.
Alder, 14" dia., bears N.55°E., 139 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13773-4)

The cor. of secs. 14, 15, 22 & 23, determined at rec. bearing & distance from the orig. NW BT:
A maple, 48" dia., bears N.63°W., 30 lks. with old axe marks on the bark.

At the corner point
Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap marked:
T25S R8W
S 15 | S 14
S 22 | S 23
1965

from which new BTs
A hemlock, 17" dia., bears N.12°E., 27½ lks., mkd: T25S R8W S14 BT.
A fir, 30" dia., bears S.86½°E., 62 lks., mkd: T25S R8W S23 BT.
A maple, 21" dia., bears S.56¼°W., 74 lks., mkd: T25S R8W S22 BT.
A fir, 29" dia., bears N.40°W., 99½ lks., mkd: T25S R8W S15 BT.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18864)

The cor. of secs. 14, 15, 22, & 23, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the only remaining original bearing tree
A maple, 45" dia., bears N.63°W., 30 lks., with bark blaze.

and bearing trees mkd. by Beck & Jelley
A hemlock, 21" diam., bears N.12°E., 27½ lks., with healed blaze.

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 35" dia., bears S.86½°E., 62 lks. with healed blaze
A maple, 45" dia. bears S.56¼°W. 74 lks. with healed blaze
A root hole, bears N.40°W., 99½ lks., with a down fir
alongside, 33" diam., with fragmentary scribe marks on
partially healed blaze.
and a new bearing tree
A fir, 34" dia., bears N.33¾°W., 146 lks., mkd. T25S R8W
S15 BT.

FD & used BLM Dependent resurvey by Timothy Moore, Cadastral
Surveyor and Robert H. Browning, Survey Tech, under Group No.
2300 surveyed May 2006- (DCSO records BLM Plat 2011-1
www.co.douglas.or.us/survmaps/CORNERS/Cadastral/Plats/2508W
& Vol. 57 Page(s) 22687)