

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3946)</p> <p>-----</p> <p>Set cedar ¼ post 3 ft. long & 3" sq. from which a Hemlock, 10" dia., bears S.60°E., 54 lks. Fir, 16" dia., bears S.65°W., 21 lks.</p>
<p>BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13776)</p> <p>-----</p> <p>Point for the ¼ sec. cor. of secs. 14 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 23" in the ground with brass cap marked:</p> <p style="text-align: center;">T25S R8W ¼ S 15 S 14 1965</p> <p>from which A fir, 10" dia., bears S.78½°E., 25 lks., mkd: ¼ S14 BT. A fir, 13" dia., bears N.54¼°W., 8½ lks., mkd: ¼ S15 BT.</p>
<p>FD & used on BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1487, surveyed May/Sept. 1989 - (DCSO records Vol. 50 Page(s) 18880)</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 4/8/2019 (Filed 11/18/2021) - C.S. File 67/50-23</p> <p>-----</p> <p>Found - 3¼" BC, marked as per record Area historically burned or shovel logged. No large stumps in the area. No orig. 1881 evidence. 8' tall x 16" D.Fir stump bears N.78½°E. 16.5'. Side center 4" mag. (Rec. SE wrong) 1964 BLM 6' x 21" D.Fir stump bears N.54¼°W., 5.2' (Rec. 5.61 ft) 1964 BLM</p> <p>New - 1 ft. tall x 20" D.Fir stump bears S.41°E., 6.1 ft. 6" tall x 14" D.Fir stump bears S.32°W., 15.0 ft.</p> <p>Note - Top center 4" mag. nail. Compass decl. 14¾°E.</p>
<p> </p>