

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3946)

-----

Cor. to secs. 10, 11, 14, & 15  
 Set fir post 4 ft. long 4" sq. from which a  
 Fir, 42" dia., bears S.70°E., 40 lks.  
 Maple, 12" dia., bears N.35°E., 30 lks.  
 W.Fir, 10" dia., bears N.60°W., 35 lks.  
 Fir, 10" dia., bears S.15°W., 8 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3972-3)

-----

Set a fir limb post, 3 ft. long, 4" sq. 24" in the ground for cor. of secs. 10, 11, 14, & 15 marked T25S S11 on NE, R8W S14 on SE, S15 on SW & S10 on NW faces with 2 notches on E & 4 notches on S edge from which  
 A burnt fir, 42" dia., bears N.80°30'E., 96 lks., marked T25S R8W S11 BT.  
 A fir stump, 36" dia., bears S.48°E., 39 lks., mkd: T25S R8W S14 BT.  
 A burnt fir, 30" dia., bears S.44°W., 87 lks., mkd: T25S R8W S15 BT.  
 A burnt fir, 36" dia., bears N.1°0'W., 256 lks., mkd: T25S R8W S10 BT.

No trace of old cor. of secs. 10, 11, 14, & 15. (See method of procedure)

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13776-7)

-----

The cor. of secs. 10, 11, 14, & 15, determined at rec. bearing & dist. from the remains of the BTs mdk. by Wygant in 1911:

A burned fir snag, 55" dia., bears N.80½°E., 96 lks., mkd: T25S R8W S11 BT on an open blaze.  
 A stump hole, bears S.44°W., 87 lks.

At the corner point

Set an iron post, 28" long, 2½" dia., 21" in the ground, with brass cap marked:

	T25S	R8W
	S 10 S 11	
_____	S 15 S 14	
	1965	

from which new BTs

A fir, 11" dia., bears N.17¼°E., 27 lks., mkd: T25S R8W S11 BT.

continued next page

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 13" dia., bears S.44½°E., 55 lks., mkd: T25S R8W S14 BT.  
A fir, 23" dia., bears S.62¾°W., 24 lks., mkd: T25S R8W S15 BT.  
A fir, 18" dia. bears N.81°W. 31 lks. mkd: T25S R8W S10 BT

Fd. & used on BLM Dependent resurvey by James E. Jelley, Harvey E. Wofford Wayne L. Rogers, Cadastral Surveyors under Group #926 & 958 surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16442)