TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 500637

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 3 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3975)

Set a fir post 3 ft. long 4" sq. 24" in the ground for ¼ sec. cor. common to 2 quarters of sec. 3 only, marked ¼ S3 on W face from which

A fir, 28" dia., bears N.46°W., 32 lks., mkd: ¼ S3 BT.
A laurel, 12" dia., bears N.80°W., 30 lks., mkd: ¼ S3 BT.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13780)

The ¼ sec. cor. of sec. 3 only, on the E bdy of the sec., determined at rec. bearing & dist. from the remains of the orig. BTs:

A down madrone, 14" dia, bears N.80°W., 30 lks., with illegible scribe marks visible in negative on the overgrowth.
A stump hole, bears N.46°W., 32 lks., the tree, a fir, 35" has fallen & slid down hill, mkd. with a healed blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T25S | R8W
¼
S 3
1965

from which

A hemlock, 8" dia., bears S.66°W., 30 lks., mkd: ¼ S3 BT.
A hemlock, 7" dia., bears N.60°W., 56 lks., mkd: ¼ S3 BT.

Ron Quimby - Crew: N. Fromdahl & R Vincent - 4/2019 - C.S. File 65/102-18

Found - BLM bras cap (properly mkd)
24" hemlock N.60°W., 37.0 ft. good scar.
New - 22" hemlock S.20°E., 18.3 ft. scribed ¼ S3 BT.
13" D.Fir S.76°W., 12.3 ft. scribed ¼ S3 BT.
16" Hemlock N.25°W., 20.8 ft. scribed ¼ S3 BT.
Note - Compass decl. 15½°E.