

PRIMARY CORNER DESCRIPTION West 1/4 Cor. Sec. 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3948)

Set laurel ¼ post 3 ft. long & 3" sq. from which a
Fir, 24" dia., bears N.55°E., 35 lks.
Cedar, 18" dia., bears N.58°W., 73 lks.

GLO resurvey by Morris Wygant, Compassman for Zachariah M. Derrick U.S. Dep. Surveyor, under contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3975)

Searched for, but cannot find any trace of the old ¼ sec. cor. Apportioned distance
Set a fir post, 3 ft. long, 4" sq. 24" in the ground for ¼ sec. cor. for sec. 2 only, marked ¼ S 2 on E face from which
A fir, 8" dia., bears S.70°E., 37 lks., mkd: ¼ S2 BT.
A hemlock, 6" dia., bears N.65°E., 44 lks., mkd: ¼ S2 BT.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13781)

The ¼ sec. cor. of sec. 2 only, on the W bdy of the sec. determined at rec. bearing & dist. from the SE BT & record bearing from the NE BT:
A fir, 17" dia., bears N.65°E., 34 lks., mkd. S on an opened blaze. (Rec. a hemlock 44 lks.)
A cedar, 17" dia., bears S.70°E., 37 lks., mkd. 2 BT on an opened blaze. (Rec. a fir)
At the corner point
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T25S R8W
 |
 ¼
 |
 S 2
 |
 1965

Ron Quimby - Crew: N. Fromdahl & R Vincent - 4/2019 - C.S. File 65/102-17

Found - BLM brass cap (properly mkd)
24" Fir N.65°E., 22.4 ft. good scar.
26" cedar S.70°E., 24.4 ft. good scar.
New - 15" Hemlock N.67°W., 6.2 ft. scribed ¼ S2 BT Alum. Post 1 ft. south.
Note - Compass decl. 15½°E.