

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T26-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A. R. and S.C. Flint, Under Contract #392,
dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3930)

Set Fir ¼ post 3 ft. long, 3" sq., from which a
Fir 20" dia., bears S.15°E., 29 lks. dist.
Fir 40" dia., bears N.35°W., 7 lks. dist.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
July 29, 1968 - C.S. File 54/72-8

Found - Orig. 20" now 24" Fir, turned out, hole fits bearing
and distance, S.15°E., 19.1 ft.
Orig. 40" now 48" Fir, alive, N.35°W., 4.6 ft.,
shows old bark scribe in fair condition.

Set Brass cap at cor. mkd: County Surveyors Office

T25S R8W ¼ $\frac{S}{S}$ $\frac{35}{2}$
T26S

1968

New BTs- 6" D.Fir N.82°E., 20.2 ft. mkd. "¼ S35 CS BT"

7" D.Fir S.64°E., 26.1 ft. mkd. "¼ S 2 CS BT"

Corner lies on moderate changing to steep SE. slope in old
growth and rhododendron brush.