

TOWNSHIP 25 RANGE 08 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated
May 26, 1881 (DCSO records Vol. 9 Page(s) 3943)

Set a fir ¼ post 3 ft. long 3" sq. from which a
Fir, 36" dia., bears N.20°W., 9 lks.
W.Fir, 20" dia., bears S.40°E., 27 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley,
Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept.
1964/July 1965 - (DCSO records 33 Page(s) 13762)

The ¼ sec. cor. of secs. 26 & 35, bears N.86°52'W., 41.04
chs. determined at rec. bearing & dist. from the orig. NW BT:
A fir, 36" dia., bears N.20°W., 9 lks., mkd: ¼ S BT on a
bark blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 22" in the ground, with
brass cap marked:

T 25S R8W
¼ S 26
 S 35
1964

from which new BTs:
A hemlock, 9" dia., bears N.72½°W., 15 lks., mkd: ¼ S26 BT
A hemlock, 10" dia., bears S.28°E., 45 lks., mkd: ¼ S35 BT

FD. brass cap & 2 down BTs by D. Edwards M145-60 - Oct. 2004