

TOWNSHIP 25 RANGE 8 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by - A.R. & S.C. Flint, Under Contract #392, dated May 26, 1881 (DCSO records Vol. 9 Page(s) 3944)

Set fir ¼ sec. cor. post 3 ft. long & 3" sq. from which a
Fir, 36" dia., bears S.50°W., 20 lks.
W.Fir, 6" dia., bears N.70°W., 26 lks.

BLM dependent resurvey by Donald R. Beck & John M. Jelley, Cadastral Surveyor, under group #'s 350 & 563 surveyed Sept. 1964/July 1965 - (DCSO records 33 Page(s) 13771-2)

Point for the ¼ sec. cor. of secs. 23 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 23" in the ground with brass cap marked:
T25S R8W
¼ S 23
 S 26
 1965

from which
A fir, 10" dia., bears N.42½°E., 62 lks., mkd: ¼ S23 BT.
A fir, 6" dia., bears S.75½°W., 40 lks., mkd: ¼ S26 BT.

David Edwards - For: Roseburg Resources. - 10/2004 - M 145-60

Found - BLM brass cap
12" Fir N.42½°E., 40.9'
6" Fir snag S.75°W., 26.4'
Both with healed blaze.
55" Fir S.30°W., 6.0' with K-tag (no rec.)